

HORI PEDESTRIAN LIGHT HLS-PL1 100W

Smart Ready

| | |
|---------------------------------------|-------------------------------------|
| Power / Daya LED | 100 Watt ($\pm 5\%$) |
| Efficacy / Kekuatan Cahaya | 110 Lm/W ($\pm 5\%$) |
| Luminous Flux / Lumen Sumber Cahaya | 11.000 Lm ($\pm 5\%$) |
| Operating Voltage / Tegangan Kerja | 190 - 250 VAC |
| Color Temperature / Warna Cahaya | 5000°K (4745°K ~ 5311°K) |
| Power Factor / Faktor Daya (PF) | 0,95 ($\pm 5\%$) |
| THD | 17% ($\pm 2\%$) |
| Case Material / Bahan Rumah Lampu | Aluminum Die Cast |
| Net Weight / Berat Bersih | 7,9 Kg ($\pm 5\%$) |
| CRI | 80 Ra ($\pm 5\%$) |
| Ambient Temperature / Suhu Lingkungan | -5°C ~ +45°C |
| Light Beam Angle / Sudut Pencahayaan | 120° |
| Lifetime / Umur Sumber Cahaya | 50.000 hours |
| LED CHIP / Sumber Cahaya LED | SZ-TYF |
| Degree of Protection / Skala IP | IP-66 |
| Certificate / Sertifikasi | CE EMC, CE LVD, IP-66, LM-79, IK-09 |




Dimension



* Toleransi dimensi sesuai dengan ISO/DIS 8062-4.2:2015

Illuminance Distribution Diagram



C0/C180: —
 C90/C270: —
 Field angle(10%Imax):C0/180Left:48.1 Right:106.1
 :C90/270Left:66.8 Right:86.6
 Beam Angle(50%Imax):C0/180Left:31.5 Right:89.3
 :C90/270Left:49.4 Right:69.5

ISO Illuminance Diagram

